

## TFS-1182 W/R

Intelligent Addressable Sounder and Beacon with Built-In Isolator

Teknim TFS-1182 is an internal usage fire alarm sounder with flasher and can connect directly to loop line. It can be powered by loop line and has built-in isolator to protect the loop against shortcuts. TFS-1182 supports 42 different tone and 3 different flasher mode options.

TFS-1182 has aesthetic design and low power consumption and are suitable for use with all Teknim addressable fire alarm control panels.



### General Features

- EN54-3, EN54-23 and EN54-17 Certified
- Built-in Isolator
- 95 dB Sound level
- 42 Different Sound Tone
- 3 Different Sound Level Options
- 3 Different Flasher Mode
- 3 Different Brightness Mode
- Red/White, transparent UL94 non-flammable poly carbonate plastic frame

### Technical Specifications

EN 54-23

EN 54-17

EN 54-3

	TFS-1182
Power	32VDC
Average Consumption	~120 µA
Alarm Consumption	Norm.=11 mA (Factory Default Setting)
Sound Level	Min: 75 dB / Norm: 85 dB (Factory Default Setting) / Max: 95 dB ±2 (at 1 meter)
Sound Tone	42 Different Tone
Sounder Type	Type A device
Piezo	Piezo with leakproof seal
Leds	Wide Range Red/White Bright LED (7 Pcs)
Notification Led	White Led (3 Pcs) <i>The device is in normal working condition 20s flashing</i>
IP Class	IP21C
Operating Temperature Range	-10 °C ~ +55 °C
Usage Area	Internal use in building
Coverage Area	W-2,4-4
Humidity	Between %0 - %95 at +40°C
Dimentions (Base Included)	Ø:110mm, h:55mm
Body Material	Red, White (Transparent) / Polycarbonate
Cable Selection	0.8mm <sup>2</sup> ~ 2.5mm <sup>2</sup>
Weight (Base Included)	207gr