

TFD-2371

Intelligent Addressable Multi Detector (Optical Smoke and Heat) with Built-in Isolator

TFD-2371 and TFD-2370 detectors use a combination of optical and heat detection technologies to sense fire and it can be connected two-wired loop circuit carrying both data and power. It uses FlashLink communication protocol to communicate Teknim Addressable control panels. It has a series of algorithms to minimize faulty detections and provide pollution warning. Sensitivity levels are adjustable through control panel or configuration software. Smoke chamber can be easily removed for cleaning in case of possible pollutions in excessively dusty environments.

The operating logic of the detector can be selected from the control panel or software. Detector can work as "Only Smoke", "Only Heat", "Smoke and Heat", "Smoke or Heat".



EN 54-5

EN 54-7

EN54-17

General Features

- EN54-7, EN54-5 and EN54-17 Certified
- Detector supports optical smoke and heat sensing technologies
- Detector can be operating in 4 different types. Only Smoke, Only Heat, Smoke and Heat, Smoke or Heat
- Supports built-in Isolator (TFD-2371)
- Supports 2x LED indicators enables 360° view
- Supports Three different colors of indication by LEDs to individually display Status, Fire Alarm, Short-Circuit and Pollution (Blink Blue/Red/Fixed Blue/Yellow)
- 3 different detection sensitivities adjustable from the control panel and configuration software (High, Medium, Low)
- Special software algorithms to eliminate sudden dust, smoke, etc. which may cause faulty alarms
- Adaptive protection preventing faulty alarms by sampling the environment continuously
- Advanced pollution algorithm that continuously measures pollution level and warns the user from detector and panel
- Supports remote indicator connection terminals
- Easy to clean smoke chamber
- Aesthetic and elegant design fits any environment
- Optional Label apparatus can be installed to the bottom of detector base view detector address from distance

Technical Specifications

	TFD-2371	TFD-2370
Standard	EN 54-5 / 7 / 17	EN54-5 / 7
Operating Type	Optical / Heat	
Built-in Isolator	Yes	No
Detection Level	H:0,12 - m:0,15 - l:0,18 dB/m	
Power	18-32VDC	
Average Consumption	80µA@32V	
Alarm Consumption	3mA	
Indicator Current	10mA	
Starting Time	15sec	
Weight (Include Base / Not)	183gr / 125gr	
Dimensions (mm)	Ø110, h42	
Body Material and Color	ABS Plastic - White	
Alarm Indicator LED	RED	
Status LED	Blue	
Isolator LED	Yellow	No
Operating Temperature	10°C ~ 70°C	
Humidity	95% RH	
Protection Class	IP30	